

WALL MOUNTED TZ COMPACT STYLE INVERTER • R32 GAS



TZ compact indoor size

The new TZ indoor units have a new size. With 799mm of width, you can put the air conditioner on the top of the door. New TZ Inverter models are powerful and efficient, with an outstanding energy ranking of A++/A+, unique in the market! The TZ works up to an outdoor temperature of -15°C in heating mode and -10°C up to an outdoor temperature of -15°C in heating and -10°C in cooling and still with a high efficiency and capacity! Furthermore, the annual energy consumption has never been so low.



Technical focus

- **NEW!** New compact design with 799mm
- R32 gas environmental friendly
- Aerowings to control air draft direction
- PM2,5 Filter to create clean and comfort indoor quality
- Complete line-up of standard Inverter models
- Super Quiet! Only 20dB(A)
- High energy savings
- This units can be installed on R410A and R22 pipings
- Long connection distance (from 15m up to 30m)
- Wired control (Optional)
- Smartphone control (Optional)

Kit			KIT-TZ20-TKE	KIT-TZ25-TKE	KIT-TZ35-TKE	KIT-TZ42-TKE	KIT-TZ50-TKE	KIT-TZ60-TKE	KIT-TZ71-TKE
Cooling capacity	Nominal (Min - Max)	kW	2,00 (0,75 - 2,40)	2,50 (0,85 - 3,00)	3,50 (0,85 - 3,90)	4,20 (0,85 - 4,60)	5,00 (0,98 - 5,60)	6,30 (0,98 - 7,10)	7,10 (0,98 - 8,10)
EER ¹⁾	Nominal (Min - Max)	W/W	3,92 (3,00 - 3,87) A	3,79 (3,40 - 3,37) A	3,50 (3,33 - 3,28) A	3,33 (3,21 - 2,79) A	3,40 (3,44 - 3,24) A	3,26 (3,50 - 2,98) A	3,17 (2,33 - 3,03)
SEER			6,40 ◀A++	6,40 ◀A++	6,20 ◀A++	5,80 ◀A+	6,80 ◀A++	6,50 ◀A++	6,10 ◀A++
Pdesign (cooling)		kW	2,0	2,5	3,5	4,2	5,0	6,3	7,1
Input power cooling	Nominal (Min - Max)	kW	0,51 (0,25 - 0,62)	0,66 (0,25 - 0,89)	1,00 (0,26 - 1,19)	1,26 (0,265 - 1,65)	1,47 (0,29 - 1,73)	1,93 (0,28 - 2,38)	2,24 (0,42 - 2,67)
Annual electricity consumption (cooling) ²⁾		kWh/a	255	330	500	630	735	339	407
Heating capacity	Nominal (Min - Max)	kW	2,70 (0,70 - 3,60)	3,30 (0,80 - 4,10)	4,00 (0,80 - 5,10)	5,00 (0,80 - 6,80)	5,80 (0,98 - 7,80)	7,20 (0,98 - 8,50)	8,60 (0,98 - 9,90)
Heating capacity at -7°C		kW	2,14	2,70	3,30	3,90	4,79	5,24	6,13
COP ³⁾	Nominal (Min - Max)	W/W	4,03 (3,78 - 3,46) A	4,13 (4,10 - 3,63) A	3,81 (4,00 - 3,59) A	3,70 (4,00 - 3,32) A	3,77 (2,88 - 3,39) A	3,44 (2,88 - 3,15) B	3,51 (2,45 - 3,47) B
SCOP			4,10 ◀A+	4,20 ◀A+	4,20 ◀A+	3,80 ◀A	4,30 ◀A+	4,20 ◀A+	4,00 ◀A+
Pdesign at -10°C		kW	1,9	2,4	2,8	3,6	4,0	4,6	5,5
Input power heating	Nominal (Min - Max)	kW	0,67 (0,19 - 1,04)	0,80 (0,20 - 1,13)	1,05 (0,20 - 1,42)	1,35 (0,20 - 2,05)	1,54 (0,34 - 2,30)	2,09 (0,34 - 2,70)	2,45 (0,40 - 2,85)
Annual electricity consumption (heating) ²⁾		kWh/a	649	800	933	1.326	1.302	1.533	1.925
Indoor Unit			CS-TZ20TKEW	CS-TZ25TKEW	CS-TZ35TKEW	CS-TZ42TKEW	CS-TZ50TKEW	CS-TZ60TKEW	CS-TZ71TKEW
Air volume	Cooling / Heating	m³/min	10,0 / 10,9	10,9 / 11,6	11,8 / 12,5	12,3 / 12,9	19,9 / 20,8	20,8 / 21,4	20,0 / 22,0
Moisture removal volume		L/h	1,3	1,5	2,0	2,4	2,8	3,5	4,1
Sound pressure ³⁾	Cooling (Hi / Lo / Q-Lo)	dB(A)	37 / 25 / 20	40 / 26 / 20	42 / 30 / 20	44 / 31 / 29	44 / 37 / 34	45 / 37 / 34	47 / 38 / 35
	Heating (Hi / Lo / Q-Lo)	dB(A)	38 / 26 / 22	40 / 27 / 22	42 / 33 / 22	44 / 35 / 28	44 / 37 / 34	45 / 37 / 34	47 / 38 / 35
Dimensions / Net weight	H x W x D	mm / kg	290 x 799 x 197 / 8	290 x 799 x 197 / 8	290 x 799 x 197 / 8	290 x 799 x 197 / 8	302 x 1.102 x 244 / 12	302 x 1.102 x 244 / 12	302 x 1.102 x 244 / 13
Outdoor Unit			CU-TZ20TKE	CU-TZ25TKE	CU-TZ35TKE	CU-TZ42TKE	CU-TZ50TKE	CU-TZ60TKE	CU-TZ71TKE
Power source		V	230	230	230	230	230	230	230
Recommended fuse		A	16	16	16	16	16	20	—
Connection (indoor/outdoor)		mm²	4 x 1,5	4 x 1,5	4 x 1,5	4 x 1,5	4 x 2,5	4 x 2,5	—
Air volume	Cooling / Heating	m³/min	31,2 / 29,7	30,0 / 28,9	28,7 / 30,4	33,6 / 34,0	33,0 / 32,2	42,6 / 41,5	44,7 / 48,1
Sound pressure ³⁾	Cooling / Heating (Hi)	dB(A)	46 / 47	47 / 48	48 / 50	49 / 51	48 / 49	49 / 49	52 / 54
Dimensions ⁴⁾ / Net weight	H x W x D	mm / kg	542 x 780 x 289 / 26	542 x 780 x 289 / 27	542 x 780 x 289 / 32	619 x 824 x 299 / 32	619 x 824 x 299 / 40	695 x 875 x 320 / 42	695 x 875 x 320 / 49
Piping connections	Liquid pipe / Gas pipe	Inch (mm)	1/4 (6,35) / 3/8 (9,52)	1/4 (6,35) / 3/8 (9,52)	1/4 (6,35) / 3/8 (9,52)	1/4 (6,35) / 1/2 (12,70)	1/4 (6,35) / 1/2 (12,70)	1/4 (6,35) / 1/2 (12,70)	1/4 (6,35) / 5/8 (15,88)
Piping length range / Elevation difference (in/out)		m	3 - 15 / 15	3 - 15 / 15	3 - 15 / 15	3 - 15 / 15	3 - 20 / 15	3 - 30 / 15	3 - 30 / 25
Pipe length for additional gas / Additional gas amount		m / g/m	7,5 / 10	7,5 / 10	7,5 / 10	7,5 / 10	7,5 / 15	7,5 / 15	10 / 25
Refrigerant (R32)		kg / TCO ₂ Eq.	0,58 / 0,392	0,67 / 0,452	0,77 / 0,520	0,86 / 0,581	1,14 / —	1,11 / 0,749	1,32 / 0,891
Operating range	Cooling Min - Max	°C	-10 ~ +43	-10 ~ +43	-10 ~ +43	-10 ~ +43	-10 ~ +43	-10 ~ +43	-10 ~ +43
	Heating Min - Max	°C	-15 ~ +24	-15 ~ +24	-15 ~ +24	-15 ~ +24	-15 ~ +24	-15 ~ +24	-15 ~ +24

Accessories	
PA-AC-WIFI-1	Full bidirectional Wifi interface for Internet control
PAW-IR-WIFI-1	IR Wifi interface for Internet control

Accessories	
CZ-RD514C	Wired remote controller for wall type
CZ-CAPRA1	H Generation interface to ECOi control integration

1) EER and COP classification is at 230V in accordance with EU directive 2002/31/EC. 2) The annual energy consumption is calculated in accordance with the ErP directive. 3) The Sound pressure of the units shows the value measured of a position 1m in front of the main body and 0,8m below the unit. The sound pressure is measured in accordance with Eurovent 6/C/006-97 specification. Q-Lo: The lowest fan speed. Lo: The second lowest fan speed (the lowest fan speed for TZ50/60). 4) Add 70mm for piping port. * Tentative values.



SEER and SCOP: For KIT-TZ50-TKE. SUPER QUIET: For KIT-TZ20-TKE, KIT-TZ25-TKE and KIT-TZ35-TKE. INTERNET CONTROL: Optional.